CSC 480/580 Principles of Machine Learning

Large Language Models (LLM)

Jason Pacheco



*some slides are from Stanford CS324

Announcements

- SCS (course survey) is open
  - 1 extra point if the response rate >= 80%

What is a language model?

- **Definition**: A language model is a probability distribution over sequences of tokens.
- token := a subword (word or part of word) // e.g., unused can be 'un' + 'used'
- $\mathcal{V}$:= the set of tokens (aka vocabulary) // e.g., $\mathcal{V} = \{\text{ate, ball, cheese, mouse, the}\}$

- A language model *p* assigns an arbitrary sequence of tokens $x_1, \ldots, x_L \in \mathcal{V}$ a probability:

$$p(x_1, \ldots, x_L)$$

  - If you grab a random person and have them say something (of L tokens), what's the probability of them saying $x_1, \ldots, x_L$?

E.g., the language model might assign:

$$p(\text{the, mouse, ate, the, cheese}) = 0.02,$$

$$p(\text{the, cheese, ate, the, mouse}) = 0.01,$$

$$p(\text{mouse, the, the, cheese, ate}) = 0.0001.$$

What is a language model?

- It's a very simplistic/holistic formulation, but developing a good one is hard.

$$p(\text{the, mouse, ate, the, cheese}) = 0.02,$$

← must be higher than the second line

"semantic knowledge"

$$p(\text{the, cheese, ate, the, mouse}) = 0.01,$$

$$p(\text{mouse, the, the, cheese, ate}) = 0.0001.$$

← must assign small probability:

"syntactic knowledge"

- Since it is a probability distribution, we can sample from it.
  - Easy for some models, and hard for some models.
  - E.g.,
    - Energy-based language models
    - Autoregressive language models are easy to sample from.

↑ designed to predict next word

Energy-based models (EBM)

- EBM defines an unnormalized score $E_\theta(x_{1:L})$ over the sequence $x_{1:L}$
- Then, the probability distribution is

$$p_\theta(x_{1:L}) = \frac{\exp\left(-E_\theta(x_{1:L})\right)}{Z_\theta}, \qquad Z_\theta = \sum_{x_{1:L}} \exp\left(-E_\theta(x)\right)$$

↑ exponential time complexity to compute this

- Sampling from this is a nightmare.. why?

Autoregressive language models

- Autoregressive model $p(x_{1:L})$ uses the chain rule of probability:

$$p(x_{1:L}) = p(x_1)p(x_2 \mid x_1)p(x_3 \mid x_1, x_2) \cdots p(x_L \mid x_{1:L-1}) = \prod_{i=1}^{L} p(x_i \mid x_{1:i-1}).$$

E.g., $p(\text{the, mouse, ate, the, cheese}) = p(\text{the})$
$p(\text{mouse} \mid \text{the})$
$p(\text{ate} \mid \text{the, mouse})$
$p(\text{the} \mid \text{the, mouse, ate})$
$p(\text{cheese} \mid \text{the, mouse, ate, the}).$

- With the decomposition above, it suffices to model $p(x_i \mid x_{1:i-1})$.
  - E.g., multi-class logistic regression with the number of classes as $|\mathcal{V}|$ and a fixed dimensional feature representation of $x_{1:i-1}$.

Q: Can we use SVM here?

Generation with autoregressive language models

- Generation algorithm.
- **Input**: language model p, length L , temperature T

  for $i = 1, \ldots, L$:

  $x_i \sim p(x_i \mid x_{1:i-1})$

  $x_i \propto p(x_i \mid x_{1:i-1})^{\frac{1}{T}}$ **// 'annealed' probability**

It's a bit confusing notation..
Technically, it should be
for $i = 1, \ldots, L$:
$x_i \sim p(X_i \mid X_{1:i-1} = x_{1:i-1})$
but this is not concise (and many people don't do this)

Temperature is useful for controlling the diversity of generation.

$T \to \infty$: uniform sampling
$T \to 0$: deterministic sampling (most likely next token)

How to use a language model, if you have a good one?

- Use it as a **prior probability** to boost the system's performance
- E.g., traditional speech recognition or machine translation

// modern versions use NNs and work differently

Goal: Given speech, infer the text



E.g., speech recognition system

Solve output = $\arg\max_{\text{text}} p(\text{text} \mid \text{speech})$

$$p(\text{text} \mid \text{speech}) \propto \underbrace{p(\text{text})}_{\text{language model}} \underbrace{p(\text{speech} \mid \text{text})}_{\text{acoustic model}}.$$

// Q: which rule is this?

Why? Typically, easier to model p(speech | text) than p(text | speech)

When ambiguous from acoustic model, language model can help (recall: sematic/syntactic knowledge is encoded in language model)

E.g., The stuff he knows can lead to problems

vs

The stuffy nose can lead to problems ← would be preferred if the system is for the medical domain

Traditional language model: **n-gram**

- n-gram model: model the correlation of n consecutive words. Approximate:

$$p(x_i \mid x_{1:i-1}) \approx p(x_i \mid \underbrace{x_{i-(n-1):i-1}}_{\text{called 'context'}})$$

(history length = n-1)

- Unigram := 1-gram $p(cheese \mid the, mouse, ate, the) \approx p(cheese)$
- Bigram := 2-gram $p(cheese \mid the, mouse, ate, the) \approx p(cheese \mid the)$
- Trigram, 4-gram, 5-gram, …

Suppose we are given a corpus (e.g., the entire Wikipedia's articles)

Q: how can we estimate unigram model?

normalized word count – p(a) = count(a) / #words
e.g., (a,b,a,b,b,a,c) ⇒ p(a) = 3 / 7

Q: how can we estimate bi-gram model?

use p(b|a) = count(a,b)/count(a)

count(a,b): how many times (a,b) occurs in the corpus
e.g., (a,b,a,b,b,a,c) ⇒ count(a,b) = 2 ⇒ p(b|a) =2/3

Q: if V is the number of tokens, how much memory do we need for bi-gram models?

n-gram model

- In 2006, Google released `Web 1T 5-gram` model

The files total 24 GB compressed (gzip'ed) text files containing

Tokens	1,024,908,267,229
Sentences	95,119,665,584
Unigrams	13,588,391
Bigrams	314,843,401
Trigrams	977,069,902
Fourgrams	1,313,818,354
Fivegrams	1,176,470,663

(source: https://catalog.ldc.upenn.edu/LDC2006T13)

- **Limitations**: cannot capture long-range dependencies

UA has a new course on large language models. It will be taught by ___

- With 5-gram model, we will not be able to put 'Mihai Surdeanu'
- If we increase n to be large, it is statistically infeasible to learn n-gram model well.

count(UA, has, a, new, course, on, large, language, models, it, will, be, taught, by) = 0

(unlikely that the corpus will include this phrase..)

- Useful for speech recognition, not useful for generic language generation.

Neural language models

- Bengio'03 pioneered using neural networks for n-gram models:

$$p(\text{cheese} \mid \text{ate}, \text{the}) = \text{some-neural-network}(\text{ate}, \text{the}, \text{cheese}).$$

parameter sharing happens through NNs ⇒ statistically feasible to have a large n

interesting details:

The implementation of this strategy was done on a cluster of 1.2 GHz clock-speed Athlon processors (32 x 2 CPUs) connected through a Myrinet network (a low-latency Gigabit local area network), using the MPI (Message Passing Interface) library (Dongarra et al., 1995) for the parallelization routines. The parallelization algorithm is sketched below, for a single example $(w_{t-n+1}, \cdots, w_t)$, executed in parallel by CPU i in a cluster of M processors. CPU i (i ranging from 0 to $M-1$) is responsible of a block of output units starting at number $start_i = i \times \lceil |V|/M \rceil$, the block being of length $\min(\lceil |V|/M \rceil, |V| - start_i)$.

they ran training for 3 weeks:

to 20 epochs for the Brown corpus. On the AP News corpus we were not able to see signs of overfitting (on the validation set), possibly because we ran only 5 epochs (over 3 weeks using 40 CPUs).

* Bengio et al., "A Neural Probabilistic Language Model," 2003.

Two key NN-based architectures

- Recurrent Neural Networks (**RNNs**), including Long Short Term Memory (**LSTMs**)
  - Allowed the conditional distribution of a token to depend on the entire context $x_{1:i-1}$ (effectively $n = \infty$).
  - However, the training is not very scalable

- **Transformers** (circa 2017)
  - Returned to having fixed context length, but were much easier to train (and exploited the parallelism of GPUs). Also, could be made "large enough" for many applications (GPT-5 uses $n = 400{,}000$).

“Large” language model

Model	Organization	Date	Size (# params)
ELMo	AI2	Feb 2018	94,000,000
GPT	OpenAI	Jun 2018	110,000,000
BERT	Google	Oct 2018	340,000,000
XLM	Facebook	Jan 2019	655,000,000
GPT-2	OpenAI	Mar 2019	1,500,000,000
RoBERTa	Facebook	Jul 2019	355,000,000
Megatron-LM	NVIDIA	Sep 2019	8,300,000,000
T5	Google	Oct 2019	11,000,000,000
Turing-NLG	Microsoft	Feb 2020	17,000,000,000
GPT-3	OpenAI	May 2020	175,000,000,000
Megatron-Turing NLG	Microsoft, NVIDIA	Oct 2021	530,000,000,000
Gopher	DeepMind	Dec 2021	280,000,000,000

GPT-4 has about 1.7T parameters, estimates for GPT-5 vary wildly

But why large?

Surprise: “Just scaling up” these models produces new emergent behavior, leading to qualitatively different capabilities and qualitatively different societal impact.

LLM Capabilities

- Conditional generation: given a prompt, generate a completion

$$\text{Frederic, Chopin, was, born, in} \overset{T=0}{\rightsquigarrow} \text{1810, in, Poland}$$

  - If we set the prompt as a question, then it results in an answer.
  - We can also ask them to write a news article, provided various levels of details.

- In-context learning: LLMs learn something from the prompt

Without instruction, the LLM figures out that the task is translating English to French

cat → chat
dog → chien
house → ?

maison

In-context learning: more examples

prompt:

```
1. Lion:
   Description: The lion is a large carnivorous mammal known for
its majestic mane and strong physique. It is often referred to
as the king of the jungle.

2. Dolphin:
   Description: The dolphin is a highly intelligent marine
mammal known for its playful nature and acrobatic skills. It is
often found in oceans and seas.

3. Elephant:
   Description: The elephant is a massive herbivorous mammal
with a long trunk and large, curved tusks. It is known for its
incredible strength and gentle nature.

Now, generate descriptions for the following animals:

4. Penguin:

5. Giraffe:

6. Cheetah:
```

response:

Here are the descriptions for the additional animals:

Penguin: Description: The penguin is a flightless bird known for its distinctive black and white plumage and upright posture. It is a highly adaptable species, often found in cold climates like the Antarctic, where it thrives by swimming and diving in search of food.

Giraffe: Description: The giraffe is a tall herbivorous mammal with an extremely long neck and legs. It is known for its spotted coat and graceful movement. Giraffes are typically found in African savannas and are the tallest land animals, feeding on leaves from the tops of trees.

Cheetah: Description: The cheetah is a sleek and fast carnivorous mammal, famous for being the fastest land animal. Its slender body and distinctive black tear markings around the eyes help it blend into its environment. Cheetahs are found in open grasslands and are known for their incredible speed when chasing prey.

Learns the expected format and style of writing!

Often called “few-shot learning”: learns patterns from only a few examples

How to use a language model?

- ChatGPT for generic conversational agent
- Conditional generation:

2B: 2 billion parameters

it: instruction fine-tuned

E.g., in Google Gemma2 2B model (`gemma2-2-it`).

Input:

```
<bos><start_of_turn>user
Write me a poem about Machine
Learning.<end_of_turn>
<start_of_turn>model
```

Note: Special tokens like <start_of_turn> work as a ‘protocol’

Output:

```
<bos><start_of_turn>user
Write me a poem about Machine Learning.<end_of_turn>
<start_of_turn>model
In silicon valleys, a mind takes flight,
No flesh and bone, but logic's light.
Machine learning, a whispered name,
A digital brain, a future's flame.

From data's depths, a pattern's gleam,
Algorithms dance, a vibrant dream.
Neural networks, a web so vast,
Learning, growing, forever to last.


… (omitted) …

<end_of_turn>
```

Try it yourself: jupyter notebook here

Google Colab kindly provides a free GPU resource.

Create a Google Colab notebook and change runtime type



be sure to choose “T4 GPU”

Usually, you can only use up to like 3 hours.

It may be interrupted suddenly (though it does not happen frequently).

note: nowadays, they allow Colab pro version for free, and you won’t have these restrictions!

Google Gemma 2, 2B parameter version

(one of the best non-stupid and small model in 2024)

1. import modules



Hugging Face

```
import transformers
from transformers import AutoTokenizer, AutoModelForCausalLM
import torch
```


// causal means the autoregressive model

2. load models (takes ~5 minutes)

```
from huggingface_hub import login
login(”..")   // signup huggingface, generate token,
                copy-paste it here

model_id = "google/gemma-2-2b-it"
dtype = torch.bfloat16

tokenizer = AutoTokenizer.from_pretrained(model_id)
model = AutoModelForCausalLM.from_pretrained(
    model_id,
    device_map="cuda",
    torch_dtype=dtype,)
```



3. prompt it

```
chat = [
   { "role": "user", "content": "Write me a poem about Machine Learning." },
]
prompt = tokenizer.apply_chat_template(chat, tokenize=False, add_generation_prompt=True)

inputs = tokenizer.encode(prompt, add_special_tokens=False, return_tensors="pt")      // obtains a sequence of token indices
outputs = model.generate(input_ids=inputs.to(model.device), max_new_tokens=1000)     maximum # of tokens to generate
print(tokenizer.decode(outputs[0]))
```

prompt: <bos><start_of_turn>user
Write me a poem about Machine
Learning.<end_of_turn>
<start_of_turn>model

(Note: Special tokens work as a ‘protocol’)

Output

<bos><start_of_turn>user
Write poem about Machine Learning.<end_of_turn>
<start_of_turn>model
In silicon valleys, a mind takes flight,
No flesh and bone, but logic's light.
Machine learning, a whispered name,
A digital brain, a future's flame.

Data flows, a river wide,
Through algorithms, it does glide.
Patterns emerge, a hidden dance,
Machine learning, a knowing glance.

From images seen, to words untold,
It learns and grows, a story unfolds.
Predicting trends, with unseen might,
A future shaped, by day and night.

In healthcare, it heals and saves,
Diagnosing diseases, a helping wave.
In finance, it guides with keenest eye,
Spotting fraud, where secrets lie.

In self-driving cars, it takes the wheel,
Navigating roads, a futuristic zeal.
In music, it composes, a soulful art,
A symphony of data, a beating heart.

But questions linger, a whispered plea,
Of ethics and bias, for all to see.
Can machines truly understand,
The human soul, the beating hand?

The future beckons, a path unknown,
Where machine learning, will surely be shown.
A tool for good, or a power to wield,
The choice is ours, the future revealed.
<end_of_turn>

model.generate(input_ids=inputs.to(model.device), max_new_tokens=1000, do_sample=True)

use this option to allow generating different completions every time you run

The raw language model before instruction fine-tuning.

↑ further training with prompt-response pairs

1. import modules

```
import transformers
from transformers import AutoTokenizer, AutoModelForCausalLM
import torch
```

2. load models (takes 2-3 minutes)

```
from huggingface_hub import login
login(”..")    // signup huggingface, generate token,
                  copy-paste it here

model_id = "google/gemma-2-2b"    // without suffix ‘-it’: this is the raw language model trained on gigantic corpus, nothing else.
dtype = torch.bfloat16

tokenizer = AutoTokenizer.from_pretrained(model_id)
model = AutoModelForCausalLM.from_pretrained(
    model_id,
    device_map="cuda",
    torch_dtype=dtype,)
```

3. prompt it

```
context = "I feel so tired today.. "
inputs = tokenizer.encode(context, return_tensors="pt")
outputs = model.generate(input_ids=inputs.to(model.device), max_new_tokens=300)
print(tokenizer.decode(outputs[0]))
```

context = "I feel so tired today.. "

<bos>I feel so tired today..

I'm not sure if it's because I'm sick or if it's because I'm just so tired of everything.

I'm tired of the way I feel.

I'm tired of the way I look.

I'm tired of the way I act.

I'm tired of the way I think.

I'm tired of the way I feel about myself.

I'm tired of the way I feel about others.

I'm tired of the way I feel about the world.

I'm tired of the way I feel about myself.

I'm tired of the way I feel about others.

I'm tired of the way I feel about the world.

I'm tired of the way I feel about myself.

I'm tired of the way I feel about others.

I'm tired of the way I feel about the world.

I'm tired of the way I feel about myself.

I'm tired of the way I feel about others.

I'm tired of the way I feel about the world.

I'm tired of the way I feel about myself.

I'm tired of the way I feel about others.

I'm tired of the way I feel about the world.

I'm tired of (reached the maximum length)

this loop is a well-known issue with the greedy decoding (i.e., choosing the most likely next token)!

The same context, but with do_sample=True

<bos>I feel so tired today..

This weekend was one of the roughest of my entire life. I have felt lost and I don't know what is happening. Everyone is talking to me like I am a child and I don't understand my life at 18. I can't handle anything this week. My ex came to visit me in my house today and he didn't even see me and talk to me. No one else in my family has talked to him and I am so hurt. I haven't even seen my ex for almost TWO MONTHS now. I don't even understand who is going to support me.

My best friend is talking to me and saying that I am so ungrateful on everything. (Which I am not!) Everyone is just so lost and not caring. I don't understand why people are like this!

I am so upset and frustrated about this all weekend. It sucks!

I never thought things would be so bad before my ex came to my house today.

He is taking the credit at this point. I don't know how else to describe this.

I am going insane. I don't think I want to live anymore. I am so sick and tired of being depressed, sad and all negative things. I feel like this is a good way out from all this, this is just the worst, I can't stand this anymore.

I am so sick and tired of everything. I don't know (reached the maximum length)

context = "It was the beginning of Summer 2003."

<bos>It was the beginning of Summer 2003. I was a 20-year-old college student, and I was in the middle of a summer internship at a small, local newspaper. I was working in the newsroom, and I was assigned to cover a story about a local high school football team.

The team was having a tough season, and the coach was under a lot of pressure. I was assigned to write a story about the team's struggles, and I was given a deadline of 10:00 a.m. the next day.

I started my research, and I found out that the team had a lot of talented players, but they were struggling because of a lack of leadership. I also found out that the coach was under a lot of pressure because he was trying to turn the team around.

I started writing my story, and I was feeling pretty good about it. I was confident that I would be able to get the story out on time.

But then, I got a call from the editor. He told me that the story was going to be published in the next day's paper, and that I had to get it out by 10:00 a.m. the next day.

I was shocked. I had never been given such a short deadline before, and I was worried that I wouldn't be able to get the story out on time.

But I was determined to get the story out on time. I started working on (reached the maximum length)

Recap: Two-kinds of LLMs

- Base model (“Autocomplete”), e.g., Gemma2-2b, GPT-3
- Instruction following model (“Chatbot”): e.g., Gemma2-2b-it, ChatGPT

Prompt = “I feel so tired today”

Autocomplete response: I feel so tired today and I think I might have not slept well last night and sometimes when people are tired they also feel low energy..

Chatbot response: Sorry to hear that. It might help to take a short break, hydrate, or rest if you can. If this keeps happening, it could be worth checking your sleep schedule or workload.

How are these models trained?



every ~year

Stage 1: Pretraining
1. Download ~10TB of text.
2. Get a cluster of ~6,000 GPUs.
3. Compress the text into a neural network, pay ~$2M, wait ~12 days.
4. Obtain **base model**.



every ~week

Stage 2: Finetuning
1. Write labeling instructions
2. Hire people (or use scale.ai!), collect 100K high quality ideal Q&A responses, and/or comparisons.
3. Finetune base model on this data, wait ~1 day.
4. Obtain **assistant model.**
5. Run a lot of evaluations.
6. Deploy.
7. Monitor, collect misbehaviors, go to step 1.

(Andrej Karpathy)

Modeling

- tokenization
- encoder/decoder
- RNN
- transformers

Tokenization

Any language model first applies tokenization.

A **tokenizer** converts any string into a sequence of tokens.

the mouse ate the cheese ⇒ [**the, mouse, ate, the, cheese**]

⇒ [1, 232, 32, 1, 39] indices

How to develop a good tokenizer?

Naïve tokenizer

- Given: A large corpus (e.g., Wikipedia)
- Algorithm:
  - Do `text.split(‘ ‘)`
  - Save all the unique words and create two dictionaries:

word → index, index → word

- How to use: Given an input text, apply text.split(‘ ‘) and then use the dictionary to get indices, then pass it down to the LM.

- Problems
  - Languages without space (e.g., Chinese)
  - Long compound words (e.g., Abwasserbehandlungsanlange)
  - Hyphenation in English: e.g., father-in-law

// don’t want to treat it as a single meaning

Tokenization: Tradeoffs

- LM treats each token as something that carries semantics and assign vector representations (parameter to be learned)

large vocabulary ⇒ more parameters!

- If we use short tokens (e.g., token=character)
  - GOOD: fewer parameters to learn
  - BAD: same token could have very different meanings

e.g., 'a' in 'apple' vs 'a' in 'angry'

parameters are shared too much

- If we use long tokens (e.g., tokens=sentence)
  - GOOD: Each token's meaning has less ambiguity
  - BAD: The # of tokens will be large ⇒ large number of parameters to learn

e.g., "I ate a tomato" vs "She ate a tomato"

parameters are not much shared

- Desiderata: just right amount of sharing parameters

Smart Tokenizer: Byte pair encoding (BPE)

Intuition: Start from character-level tokenizer and then combine tokens that co-occur frequently.

- Input: a training corpus (sequence of characters).
- Initialize the vocabulary $\mathcal{V}$ be the set of characters.
- While we want to still grow $\mathcal{V}$: // we need to somehow decide when to stop. (e.g., until the vocab size is $\leq$ a preset value)
  - Find the pair of elements $x, x' \in \mathcal{V}$ that co-occur the most number of times.
  - Replace all occurrences of x, x' with a new symbol xx'.
  - Add xx' to $\mathcal{V}$. ← note: we are not going to throw away x, x' !


Example:

1	[t, h, e, ␣, c, a, r], [t, h, e, ␣, c, a, t], [t, h, e, ␣, r, a, t]	$\mathcal{V} = \{t, h, e, c, a, r\}$
2	[th, e, ␣, c, a, r], [th, e, ␣, c, a, t], [th, e, ␣, r, a, t] (*th* occurs 3x)	$\mathcal{V} = \{t, h, e, c, a, r, th\}$
3	[the, ␣, c, a, r], [the, ␣, c, a, t], [the, ␣, r, a, t] (*the* occurs 3x)	$\mathcal{V} = \{t, h, e, c, a, r, th, the\}$
4	[the, ␣, ca, r], [the, ␣, ca, t], [the, ␣, r, a, t] (*ca* occurs 2x)	$\mathcal{V} = \{t, h, e, c, a, r, th, the, ca\}$

How to apply tokenizer

We need to apply the merging in the order that was collected in the algorithm!

merges = $\{(t, h), (th, e), (c, a)\}$




Andriy Burkov
@burkov

In doing research for my book, I discovered that byte-pair encoding (BPE), the algorithm used to tokenize data for modern language models, one of the most important algorithms of our times, is described incorrectly in almost all online resources. Once the BPE model is trained, most explain the process of tokenizing a new sequence as scanning it from left to right and looking for the longest token in the vocabulary that matches the upcoming characters.

This is not how it works, and doing so would not result in correct tokenization. The real algorithm takes a word, checks if the word is also a token, and if it is, it returns the token. If not, the word is split into individual characters, and those characters are merged by using the learned merge rules in the same order those rules were added to the merges collection during BPE training.

Don't trust online information. Trust the source code and good books.



```
def tokenize_word(word, merges, vocabulary, charset, unk_token="<UNK>"):
    word = '_' + word ❶
    if word in vocabulary:
        return [word] ❷
    tokens = [char if char in charset else unk_token for char in word] ❸

    for left, right in merges: ❹
        i = 0
        while i < len(tokens) - 1: ❺
            if tokens[i:i+2] == [left, right]: ❻
                tokens[i:i+2] = [left + right] ❼
            else:
                i += 1 ❽
    return tokens
```

This function tokenizes a `word` using the `merges` and `charset` from `byte_pair_encoding`. Unknown characters are replaced with `unk_token`.

Line ❶ prepends a boundary marker to the input `word`. Line ❷ returns the `word` if it's part of the `vocabulary`. Otherwise, the algorithm proceeds to the subword tokenization.

Line ❸ converts the word into a list of characters, replacing those not in `charset` with `unk_token`. Line ❹ loops through all merge rules, unpacking each merge into `left` and `right`.

The inner loop at line ❺ iterates through `tokens` in pairs. Line ❻ checks if a pair matches the merge. If it matches, line ❼ combines the pair into one token. Otherwise, line ❽ moves to the next pair. The function runs until all merges are applied and then returns the tokenized word.

Example: Gemma 2's tokenizer

```
[4]  context = "I feel so tired today.. "
     inputs = tokenizer.encode(context, return_tensors="pt")
```

```
[5]  inputs
```

```
tensor([[     2, 235285,   2375,    712,  17955,   3646,    723, 235248]])
```

```
[7]  tokenizer.convert_ids_to_tokens(inputs[0])
```

```
['<bos>', 'I', '_feel', '_so', '_tired', '_today', '..', '_']
```

beginning of sentence token (actually, beginning of text)

underscore to denote that it came after a space!

```
context = "He and I went to the hospital."
input = tokenizer.encode(context, return_tensors="pt")
print(input)
tokenizer.convert_ids_to_tokens(input[0])
```

```
tensor([[     2,   1949,    578,    590,   3815,    577,    573,   7454, 235265]])
['<bos>', 'He', '_and', '_I', '_went', '_to', '_the', '_hospital', '.']
```

I vs _I : they are treated differently!

Example: Gemma 2's tokenizer

```
tokenizer.vocab_size
```

```
256000
```

```
tokenizer.vocab
```

```
{'褒': 245731,
 '傈': 252315,
 '_madd': 140497,
 '_Eccl': 220305,
 '짹': 255359,
 '_погиб': 145861,
 'oot': 152782,
 'Frequency': 36778,
 'paña': 14962,
 '126290 :'عتبر,
 '")': 34084,
 '_UserDao': 192028,
 '"]).': 193268,
 '_212714 :'מול,
 'チョコ': 71374,
 'DIY': 56383,
 'ℏ': 243145,
 '_HES': 203183,
 '_로그': 202886,
 '_Industries': 33731,
 '_vacunación': 167312,
 '\x03': 249006,
 'Bund': 94648,
```


dictionary mapping from token to index

Modeling

- tokenization
- encoder/decoder
- transformers

Word embedding: Where all the powers come from

- Word embedding: use a vector to represent each word whose geometric relationship captures semantic relationship



Efficient Estimation of Word Representations in Vector Space

Tomas Mikolov
Google Inc., Mountain View, CA
tmikolov@google.com

Kai Chen
Google Inc., Mountain View, CA
kaichen@google.com

Greg Corrado
Google Inc., Mountain View, CA
gcorrado@google.com

Jeffrey Dean
Google Inc., Mountain View, CA
jeff@google.com

paper in NeurIPS'13; received test-of-time award from NeurIPS'23

example, word *big* is similar to *bigger* in the same sense that *small* is similar to *smaller*. Example of another type of relationship can be word pairs *big - biggest* and *small - smallest* [20]. We further denote two pairs of words with the same relationship as a question, as we can ask: "What is the word that is similar to *small* in the same sense as *biggest* is similar to *big*?"

Somewhat surprisingly, these questions can be answered by performing simple algebraic operations with the vector representation of words. To find a word that is similar to *small* in the same sense as *biggest* is similar to *big*, we can simply compute vector $X = vector("biggest") - vector("big") + vector("small")$. Then, we search in the vector space for the word closest to X measured by cosine distance, and use it as the answer to the question (we discard the input question words during this search). When the word vectors are well trained, it is possible to find the correct answer (word *smallest*) using this method.

- (Mikolov et al, 2013) trained vector representations so it can predict words given surrounding words.
- Used Google News corpus for training
  - The training objective is to learn word vector representations that are good at predicting the nearby words.

Type of relationship	Word Pair 1		Word Pair 2	
Common capital city	Athens	Greece	Oslo	Norway
All capital cities	Astana	Kazakhstan	Harare	Zimbabwe
Currency	Angola	kwanza	Iran	rial
City-in-state	Chicago	Illinois	Stockton	California
Man-Woman	brother	sister	grandson	granddaughter

Contextual Embedding

- Limitation of the word embedding: Each word can mean different things given context..
- Let's make it contextual! ⇒ this is the core of modern LLMs!

$$[\text{the, mouse, ate, the, cheese}] \overset{\phi}{\Rightarrow} \left[\begin{pmatrix}1\\0.1\end{pmatrix}, \begin{pmatrix}0\\1\end{pmatrix}, \begin{pmatrix}1\\1\end{pmatrix}, \begin{pmatrix}1\\-0.1\end{pmatrix}, \begin{pmatrix}0\\-1\end{pmatrix}\right].$$

- As the name suggests, the contextual embedding of a token depends on its context (surrounding words); for example, consider **the**.
- Notation: We will $\phi : \mathcal{V}^L \to \mathbb{R}^{d \times L}$ to be the embedding function (analogous to a feature map for sequences).
- For a token sequence $x_{1:L} = [x_1, \ldots, x_L]$, ϕ produces contextual embeddings $\phi(x_{1:L})$.

L: length of the input d: dimension of the embedding

Types of language models

LLMs ≈ Contextual embedding function

Encoder only (BERT, RoBERTa, …): Special focus on **embedding** itself

$$x_{1:L} \Rightarrow \phi(x_{1:L}).$$

- Given an ML task (e.g., sentiment classification) and a dataset for it, we can build a linear classifier, treating $\phi(\cdot)$ as a feature function, and

$$[\text{[CLS]}, \text{the}, \text{movie}, \text{was}, \text{great}] \Rightarrow \text{positive}.$$

↑ 'Classification token'; often, take this token's embedding as the 'sentence embedding'

Decoder only (GPT-2, GPT-3, …): Special focus on **generation**

$$x_{1:i} \Rightarrow \phi(x_{1:i}), p(x_{i+1} \mid x_{1:i}).$$

p(.|.): typically, nothing more than multi-class logistic classifier (linear), where the input is the last column of $\phi(x_{1:i})$.

- Hope: $\phi(x_{1:i})$ summarizes information in the first i tokens necessary to predict the (i+1)-th token

Example: Decoder-only model (e.g., GPT series)

- It's complex! We'll break it down in 3 steps.
- Recall: Input is a sequence of token indices // tokenizer is assumed given

Input: $x_{1:L}$
Goal: compute $p(x_{L+1}|x_{1:L})$

Step 1: Compute token embeddings (context-*independent*)

Parameter: $E \in \mathbb{R}^{|\mathcal{V}| \times d}$ // base embedding (contextless); we will learn it from data


def $\mathbf{EmbedToken}(x_{1:L} : \mathcal{V}^L) \to \mathbb{R}^{d \times L}$: (nothing to compute, just a lookup)

- *Turns each token x_i in the sequence $x_{1:L}$ into a vector.*
- Return $[E_{x_1}, \ldots, E_{x_L}]$.

notation: E_x is the row of E corresponding to the token x

Step 2: Transformer layer (picture credit: here)


- Input: embedding of words
- Output: new embedding of words that incorporates their surrounding contexts




Attention mechanism (picture credit: here)

- Vaswani et al., “Attention Is All You Need”, 2017.
- Attention mechanism: fuzzy look-up in a key-value store

In a **lookup table**, we have a table of keys that map to values. The query matches one of the keys, returning its value.




In **attention**, the query matches all keys *softly*, to a weight between 0 and 1. The keys' values are multiplied by the weights and summed.



Recap: what's in an LLM

- Core functionality: next token prediction



- Key component 1: tokenizer
  - "Chop" raw text to a sequence of tokens, represented by their indices

```
[4]  context = "I feel so tired today.. "
     inputs = tokenizer.encode(context, return_tensors="pt")

[5]  inputs

     tensor([[     2, 235285,   2375,    712,  17955,   3646,    723, 235248]])


[7]  tokenizer.convert_ids_to_tokens(inputs[0])

     ['<bos>', 'I', '_feel', '_so', '_tired', '_today', '..', '_']
```

Recap: what's in an LLM


- Key component 2:

  Transformer network



- Given: the context (indices of previous n tokens, e.g. n=1024)
- Predict: for each token in the vocabulary $\mathcal{V}$ (e.g., $|\mathcal{V}|$ = 10000), the probability of it appearing next (a $|\mathcal{V}|$-dimensional probability vector)

Transformer network: a bird's eye view



Logistic regression to predict next token


Look at the last token's representation

Tokens' (more) context-specific representations

Obtain tokens' context-specific representations

Input context: next word may be 'are', 'operate', …


Key step:
Transformer block
(aka Transformer layer)



Word Embedding: context-independent representation

Core gadget: attention layer (picture credit: here)


- Input: embeddings of a sequence of tokens
- Output: new embeddings of these tokens that incorporates their surrounding contexts




Attention mechanism (picture credit: here)

- Vaswani et al., “Attention Is All You Need”, 2017.
- Attention mechanism: fuzzy look-up in a key-value store


In a **lookup table**, we have a table of keys that map to values. The query matches one of the keys, returning its value.



In **attention**, the query matches all keys *softly*, to a weight between 0 and 1. The keys' values are multiplied by the weights and summed.



Attention mechanism in math (part 1)



One can think of attention as a "soft" lookup table, where we have a query y that we want to match against each element in a sequence $x_{1:L} = [x_1, \ldots, x_L]$: x_i: d-dimensional embedding of token i

$[x_1, \ldots, x_L]$ y **goal**: transform the embedding of y into one that incorporates contextual influence

We can think of each x_i as representing a key-value pair via linear transformations:

$$(W_{\text{key}} x_i) : (W_{\text{value}} x_i)$$

$W_{\text{key}}, W_{\text{value}} \in \mathbb{R}^{d \times d}$

and forming the query via another linear transformation:

$$W_{\text{query}} y.$$

$W_{\text{query}} \in \mathbb{R}^{d \times d}$

The key and the query can be compared to give a score:

$$\text{score}_i = x_i^\top W_{\text{key}}^\top W_{\text{query}} y.$$

larger when y "more relevant" to token x_i

These scores can be exponentiated and normalized to form a probability distribution over the token positions $\{1, \ldots, L\}$:

$$[\alpha_1, \ldots, \alpha_L] = \text{softmax}([\text{score}_1, \ldots, \text{score}_L]).$$

Attention weights in a real Transformer network


(Ignore the colors for now; Spoiler:

colors indicate different attention heads)


y = embedding of ‘it_’

Darker line indicates larger α_i

(words more relevant to y)



Attention mechanism in math (part 2)



Then the final output is a weighted combination over the values:

$$\sum_{i=1}^{L} \alpha_i (W_{\text{value}} x_i).$$

scalar

d by 1

Summary of attention: $\text{def } \textbf{Attention}(x_{1:L} : \mathbb{R}^{d \times L}, y : \mathbb{R}^d) \to \mathbb{R}^d$:

// a way to get a transformed embedding of y influenced by the rest


- *Process y by comparing it to each x_i.*
- Return $W_{\text{value}}\, x_{1:L}\, \text{softmax}(x_{1:L}^\top W_{\text{key}}^\top W_{\text{query}} y / \sqrt{d})$.

d x d d x L L x d d x 1


* important that $W_{query} \neq W_{key}$ because it allows asymmetric influence!

Visualization

Ex: Computing ‘Thinking’ ‘s context-sensitive embedding in phrase “Thinking Machines”



Learnable embedding transformation matrices




Self-attention: attending each tokens to others

def $\mathbf{SelfAttention}(x_{1:L} : \mathbb{R}^{d \times L}) \to \mathbb{R}^{d \times L})$:

- *Compare each element x_i to each other element.*
- Return $[\mathbf{Attention}(x_{1:L}, x_1), \ldots, \mathbf{Attention}(x_{1:L}, x_L)]$.

d x 1 **d x 1**

Compute self attentions all at once: using matrices




$$\text{softmax}\left(\frac{Q \times K^T}{\sqrt{d_k}}\right) V = Z$$

The self-attention calculation in matrix form


softmax outputs 2 by 2 where each row is a probability vector!

Attention score in matrices



Visualizing self-attention (Bertviz)

(Ignore the colors for now; grayscale = attention weight)



Causal self-attention

Step 2a:

def SelfAttention($x_{1:L} : \mathbb{R}^{d \times L}$) $\rightarrow \mathbb{R}^{d \times L}$):

- *Compare each element x_i to each other element.*
- Return [$\text{Attention}(x_{1:L}, x_1), \ldots, \text{Attention}(x_{1:L}, x_L)$].

For next token prediction, instead: we'd like the contextual embedding of each token to only depend on its predecessors

Why? When training to generate, e.g., 'The capital of France is **Paris**', we'd like the contextual embedding of 'is' to not depend on 'Paris', to really learn to predict it based on previous contexts such as 'capital', 'France'

def MaskedSelfAttention($x_{1:L}$: $\mathbb{R}^{d \times L} \rightarrow \mathbb{R}^{d \times L}$)


- Compare each element x_i to each other element appeared before only
- Return [Attention(x_1, x_1), Attention($x_{1:2}, x_2$), ..., Attention($x_{1:L}, x_L$)]

Transformer block other parts: LayerNorm & Residual Connection

def $\mathbf{LayerNorm}(x_{1:L} : \mathbb{R}^{d \times L}) \to \mathbb{R}^{d \times L}$:

(recall batch normalization)

- *Make each x_i not too big or small.*



def $\mathbf{AddNorm}(f : (\mathbb{R}^{d \times L} \to \mathbb{R}^{d \times L}), x_{1:L} : \mathbb{R}^{d \times L}) \to \mathbb{R}^{d \times L}$:

- *Safely apply f to $x_{1:L}$.*
- Return $\mathbf{LayerNorm}(x_{1:L} + f(x_{1:L}))$.

do this instead of just $f(x_{1:L})$:
this is called 'residual connection'

Q: what is it for?

Mitigate vanishing/exploding gradients

Transformer block other parts: FeedForward (MLP)

def $\mathbf{FeedForward}(x_{1:L} : \mathbb{R}^{d \times L}) \to \mathbb{R}^{d \times L}$:


- *Process each token independently.*
- For $i = 1, \ldots, L$:
  - Compute $y_i = W_2 \max(W_1 x_i + b_1, 0) + b_2$.
- Return $[y_1, \ldots, y_L]$.

e.g., GPT-2 uses 2-layer neural network with the # hidden units = 4d

Q: What should the sizes of W_1 and W_2 be?

$W_1: 4d \times d$


$W_2: d \times 4d$



A full Transformer block: putting everything together

def $\mathbf{TransformerBlock}(x_{1:L} : \mathbb{R}^{d \times L}) \to \mathbb{R}^{d \times L}$:

- *Process each element x_i in context.*
- Return $\mathbf{AddNorm}(\mathbf{FeedForward}, \mathbf{AddNorm}(\mathbf{SelfAttention}, x_{1:L}))$.



Positional encoding


Token's position is important!

We need to encode each token's position information

def $\mathbf{EmbedTokenWithPosition}(x_{1:L} : \mathbb{R}^{d \times L})$:


- *Add in positional information.*
- Define positional embeddings:
  - Even dimensions: $P_{i,2j} = \sin(i/10000^{2j/d_{\text{model}}})$
  - Odd dimensions: $P_{i,2j+1} = \cos(i/10000^{2j/d_{\text{model}}})$
- Return $[x_1 + P_1, \ldots, x_L + P_L]$.

What is this doing?



Positional encoding

d=500; here, they arranged sines first and then cosines



↑ L=2000


Positional encoding values (left) and the value of the dot product of position 1000 with neighboring positions (right).

Dot product ≈ 'similarity' => higher similarity for nearby vectors!

https://www.blopig.com/blog/2023/10/understanding-positional-encoding-in-transformers/#:~:text=As%20we%20have%20seen%2C%20sinusoidal,while%20effective%2C%20has%20some%20drawbacks.

The full Transformer text encoder


$$\text{GPT-3}(x_{1:L}) = \text{TransformerBlock}^{96}(\text{EmbedTokenWithPosition}(x_{1:L}))$$



shaded ones are not part of the parameter learning

transformer diagram from Guan et al., A Knowledge-Enhanced Pretraining Model for Commonsense Story Generation

Final step: Predict next token



Logistic regression to predict next token

$$p(x_{i+1} \mid x_{1:i}) = \text{softmax}(E\phi(x_{1:i})_i).$$

E: $|\mathcal{V}|$ by d embedding matrix (we used it before!)

$\phi(x_{1:i})$: output of Transformer encoder, d by i


Use the last token's representation

$\phi(x_{1:i})_i$: taking the last column: d by 1

- Why do we reuse E, which is used in the input?

  It's parameter sharing that people found to work well!

Transformer network: altogether



$\Rightarrow$ $|\mathcal{V}|$-dimensional probability vector

$\Rightarrow$ sample a token!

Extra details: multi-headed attention

def $\mathbf{MultiHeadedAttention}(x_{1:L} : \mathbb{R}^{d \times L}, y : \mathbb{R}^d) \to \mathbb{R}^d$:


- *Process y by comparing it to each x_i with respect to n_{heads} aspects.*
- Return $W_{\text{output}}[\underbrace{\mathbf{Attention}(x_{1:L}, y), \ldots, \mathbf{Attention}(x_{1:L}, y)}_{n_{\text{heads}} \text{times}}]$.

↑ d x d


↑ each attention returns $\frac{d}{n_{\text{heads}}}$ dimension..!

Example: 12 attention heads (each color is a head)

Thus 12 pairwise attention matrices,
each induced by its respective W^Q, W^K, W^V



GPT-2 (OpenAI, 2019)



$|\mathcal{V}| = 50{,}257$

$L = 1{,}024$


$d = 768$

$d_{FF} = 768{\times}4$

(# of hidden units for Feed-forward (fully-connected) layer)

Training

Recall goal: next token prediction



Recall: Autoregressive language model = assign values to $P(x_i \mid x_{1:i-1})$

- The loss we use for multiclass logistic regression: $-\log p(y \mid x)$, which is the cross-entropy loss.

$$\min_w \sum_{i=1}^{n} -\log p(y_i \mid x_i; w)$$

- Treat x_{i+1} as the label for classification, and $x_{1:i}$ as the input feature.

# of documents in corpus

# of tokens in document j

$$\min_w \sum_{j=1}^{m} \sum_{i=1}^{n_j} -\log p\left(x_i^{(j)} \mid x_{1:i-1}^{(j)}; w\right)$$

i-th token in j-th document


w: weights (and biases) for

- embedding E
- key, query, value matrix
- fully connected layers
- layer normalization

Update the parameters using backprop (loss.backward()) & stochastic gradient descent!


Autoregressive LLM

- Transformer network



- Given: the context (indices of previous n tokens, e.g. n=1024)
- Predict: for each token in the vocabulary $\mathcal{V}$ (e.g., $|\mathcal{V}|$ = 10000), the probability of it appearing next (a $|\mathcal{V}|$-dimensional probability vector)

Batch training: idea



How many input-output pairs do we have for the highlighted text?

- input = in, output = the
- input = in the, output = morning
- input = in the morning, output = the
- input = in the morning the, output = sky
- input = in the morning the sky, output = is
- input = in the morning, the sky is, output = blue


This gives 6 cross-entropy losses.
Can they be computed in parallel?

Yes!
(And backprop can also be done in parallel)

Batch training: idea



The cross entropy losses within a sentence can be calculated in parallel!




Miscellaneous remarks

Instruction fine-tuning

- Gather question and answer pairs for your specific task.
- The training objective is the same: you want the model to assign large probability to the answers
- Perform the training with the starting point being the already trained unsupervised language model.
- Common trick: **LoRA** (Low rank adaptation)
  - We freeze the weight of a layer W
  - We replace W with $W + AB$ where $A \in \mathbb{R}^{d \times k}$ and $B \in \mathbb{R}^{k \times d}$ ($k \ll d$) are learnable parameters
  - This prevents overfitting
    - Typically, the training set for fine tuning is much smaller than the unsupervised learning counterpart!

Alignment

- Even after instruction fine-tuning, LLMs could generate undesirable answers.



"Decoding Biases: Automated Methods and LLM Judges for Gender Bias Detection in Language Models"

Alignment

- Provide two answers from an LLM, and ask humans which one is more desirable and harmless.
- Eventually, we use the data {(prompt, answer1, answer2, preference $\in \{1,2\}$)} to train.
- Two popular approaches
  - **RLHF**: Reinforcement learning with human feedback
    - Take LLMs as an agent making token generation decision.
    - Key: Use reinforcement learning where 'reward' is given as the comparison feedback
  - **DPO**: Direct policy optimization
    - Come up with a reasonable loss function to update the model directly.

- Uses a regularizer to ensure $P(x_i \mid x_{1:i-1}; \text{model after training})$ is not too different from $P(x_i \mid x_{1:i-1}; \text{initial model})$

// otherwise, it may hurt the quality of the answer

The infamous “strawberry” problem

```
# how many times does the character 'r' appear in the word 'strawberry'?
chat = [
    # { "role": "user", "content": "Write poem about Machine Learning." },
  { "role": "user", "content": "how many times does the character 'r' appear in the word 'strawberry'?" },
]
prompt = tokenizer.apply_chat_template(chat, tokenize=False, add_generation_prompt=True)
inputs = tokenizer.encode(prompt, add_special_tokens=False, return_tensors="pt")
```

```
outputs = model.generate(input_ids=inputs.to(model.device), max_new_tokens=1000)
print(tokenizer.decode(outputs[0]))
```

```
<bos><start_of_turn>user
how many times does the character 'r' appear in the word 'strawberry'?<end_of_turn>
<start_of_turn>model
The character 'r' appears **twice** in the word "strawberry".
<end_of_turn>
```

```
input = tokenizer.encode("strawberry", return_tensors="pt")
print(input)
tokenizer.convert_ids_to_tokens(input[0])
```

```
tensor([[     2, 132077]])
['<bos>', 'strawberry']
```

← ‘strawberry’ is basically ‘token 132077’

the only way the model can answer this correct is that this Q&A was in the training set


Tokenization needs improvements

Tokenization is at the heart of much weirdness of LLMs. Do not brush it off.

- Why can't LLM spell words? **Tokenization**.
- Why can't LLM do super simple string processing tasks like reversing a string? **Tokenization**.
- Why is LLM worse at non-English languages (e.g. Japanese)? **Tokenization**.
- Why is LLM bad at simple arithmetic? **Tokenization**.
- Why did GPT-2 have more than necessary trouble coding in Python? **Tokenization**.
- Why did my LLM abruptly halt when it sees the string "<|endoftext|>"? **Tokenization**.
- What is this weird warning I get about a "trailing whitespace"? **Tokenization**.
- Why the LLM break if I ask it about "SolidGoldMagikarp"? **Tokenization**.
- Why should I prefer to use YAML over JSON with LLMs? **Tokenization**.
- Why is LLM not actually end-to-end language modeling? **Tokenization**.
- What is the real root of suffering? **Tokenization**.

(from Andrej Karpathy’s tweet)

Recent updates (as of December 2024)



Model	Overall	Overall w/ Style Control	Hard Prompts	Hard Prompts w/ Style Control	Coding	Math	Creativ Writing	Instructio Following	Longer Query	Multi-Turn
gemini-exp-1206	1	1	1	1	1	1	1	1	1	1
chatgpt-4o-latest-20241120	2	1	3	4	2	4	1	2	1	1
gemini-exp-1121	2	4	2	3	3	2	1	2	2	2
o1-preview	4	3	2	1	2	1	4	2	3	3
o1-mini	5	7	2	4	1	1	16	5	5	5
gemini-1.5-pro-002	5	6	6	5	7	5	4	5	5	7
grok-2-2024-08-13	7	10	10	10	8	10	6	9	8	8
yi-lightning	7	11	6	9	6	5	6	8	6	5
gpt-4o-2024-05-13	7	6	9	9	7	10	6	8	7	7
claude-3-5-sonnet-20241022	7	4	6	2	5	5	6	6	5	5

try it:
https://aistudio.google.com/app/prompts/new_chat?model=gemini-exp-1206


- We cannot compete with industry in this weight-lifting game.
- Recent interests from academia
  - How can we best use LLMs? (e.g., prompt engineering, chain-of-thought)
  - Making LLMs small and fast
    - Improve test time complexity of transformer (length^2)
  - Mitigate potential harms from using LLMs
  - What other problems can benefit from transformer architecture?

LLM agents

- LLM enable the development of agents that can carry out tasks autonomously, on behalf of the user
- Simplest agent: chatbot

- Demo with LangGraph
  - (Google Gemini API key needed)
  - Full tutorial here






- chatbot_node takes into historical messages, and invokes an LLM to output a new response


LLM agents

- Agents can do much more by calling tools (web browsers, calculators, stock price API queries, …)
- A basic stock price summary agent built using LangGraph
- Chatbot has the option of:
  - Calling tools
  - Ending the interaction




OPENCLAW

- Open-source, personalized agent that can do many things for us



- Oops..
- Still has considerable security risks



Useful Resources

- The notebook of HW4 P2 provides a minimal working Transformer model
- GPT from scratch: jupyter notebook with pictures
- The illustrated Transformer by Jay Alammar
- Let's build GPT: from scratch, in code, spelled out

  by Andrej Karpathy

